




RIO head-end adaptor module Modicon Quantum - 1 connector with single cable

140CRP93100

① Discontinued on: 15 March 2022



140CRP93100 has not been replaced. Please contact your customer care center for more information.

Main

Range of Product	Modicon Quantum automation platform
Product or Component Type	RIO head-end adaptor module

Complementary

•	
Product Compatibility	Quantum 200/500/800 series Symax (any mix)
Maximum drops/network	31
I/O words/drop	64 I/64 O
Type of cable	75 Ohm coaxial
Transmission Rate	1544 Mbit/s
Dynamic range	35 dB
Isolation voltage	500 V DC coaxial center and ground
Electrical connection	1 female connector F, elbowed with single cable
Diagnostics startup	Power up Memory check LAN controller check
Power dissipation in W	3 W 1 channel
Marking	CE
Bus current requirement	600 mA 1 channel
Module format	Standard

Environment

Product Certifications	FM Class 1 Division 2
Standards	UL 508 CUL CSA C22.2 No 142
Resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2
Resistance to electromagnetic fields	9.14 V/m (10 V/m) 801000 MHz IEC 801-3
Ambient Air Temperature for Operation	32140 °F (060 °C)

Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Relative Humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

Ordering and shipping details

Category	18155-QUANTUM I/O & POWER SUPPLIES
Discount Schedule	PC21
GTIN	3595861133754
Number of Units in Package 1	1
Package 1 Weight	17.64 oz (500.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.69 in (4.3 cm)
Package 1 Width	6.42 in (16.3 cm)
Package 1 Length	12.36 in (31.4 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	8.60 lb(US) (3.9 kg)
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.		


Contractual warranty

Warranty	18 months	
----------	-----------	--

Dimensions Drawings

Racks for Modules Mounting

Dimensions of Modules and Racks



- 2 slots 3 slots 4 slots (1) (2) (3) (4) (5) (6)
- 6 slots
- 10 slots
- 16 slots