



NX-PD1000

NX bus power supply unit, 24 V DC input, non-isolated, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Power feed
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	2
Number of IOG (V-) terminals	2
Number of FG terminals	2
Degree of protection (IP)	IP20
Height	100 mm
Width	12 mm
Depth	71 mm
Weight	65 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



NX-TBA082

Replacement screwless push-in connector with 8 wiring terminals (marked A+B)

Downloads

CAD Library



IO-Link Series Brochure

EN PDF 6.26 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.56 MB



NX-TC Brochure

EN PDF 3.83 MB



NX-series I/O System Brochure

EN PDF 6.46 MB



NX-series System Unit - NX-PD/PF/PC/TBX Datasheet

EN PDF 3.37 MB



NX-series System Units Users Manual

EN PDF 6.18 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 9.22 MB

