



LR-XH250

Separate Amplifier Model, Sensor Head, 250mm range, 2m Cable



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model	LR-XH250	
Type	Cable Length: 2 m 6.6'	
Detecting Distance	30 to 250 mm 1.18" to 9.84"	
Standard Detectable Deviation	30 to 180 mm: 9 mm, 180 to 250 mm: 18 mm 1.18" to 7.09": 0.35", 7.09" to 9.84": 0.71	
Display Resolution	1 to 2 mm 0.04" to 0.08"	
Spot Size	Approx. 0.8 mm × 1.2 mm 0.03" × 0.05" (at a detecting distance of 250 mm 9.84")	
Light Source	Type	Green laser (505 nm)
	Laser Class	Class 1 laser product (IEC60825-1, FDA (CDRH), Part1040.10*1)
Environmental resistance	Enclosure rating	IP65/IP67 (IEC60529)
	Ambient light	Incandescent lamp: 8000 lux or less, Sunlight: 8000 lux or less
	Ambient temperature	-10°C to +50°C 14°F to 122°F (no freezing)
	Relative humidity	35 to 85% RH (no condensation)
	Vibration resistance	10 to 500 Hz; Power Spectral Density: 0.816 G ² /Hz for X, Y and Z axes
	Shock resistance	1000 m/s ² (100G); 6 times each for X, Y, and Z axes
Material	Case: SUS316L; Lens Cover: PSU; Gasket: FKM (lens cover), EVM (cable)	
Accessories	Laser warning label	
Weight	approx. 75 g	

*1 Classification performed based on IEC60825-1 standards in accordance with FDA (CDRH) Laser Notice.

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

LR-XH50_XH100_XH250

